

Wrapping film

NEWRAP™ 5

New generation film adapted for 3D-Combi machines



Blown film manufactured with high mechanical qualities



5 layer technology



Reinforced impermeability



UV protection 12 months (class A)



Availability

We can look at the possibility of other dimensions or enhanced UV protection

	Black	White	Green
Thickness	25μ		
Width x Length	Available in 500mm x 1800m or 750mm x 1500m		



Groupe
Barbier
Plastic solutions

Wrapping film

Complies with NF EN14932
25 μ



Technical specifications

	Values		Test Method
Width	500 mm	750 mm	ISO 4592
Thickness	25 microns		ISO 4591 et ISO 4593
Roll length	1800 m	1500 m	§9.4.EN14932
Stress at break	SL>28 MPa / ST >23MPa		EN ISO 527-1 EN ISO 527-3
Elongation at break	SL>400% / ST >600%		
DART TEST	400 g		EN ISO7765-1 : 2004 méthode A
Sealing	> 4 mBars		Test BARBIER

Our engagements

This commercial document has no contractual value. The information and photographs contained therein are not binding except the appreciated technical specifications in accordance with the EN14932 standard.

Only our F.I.C.C.U: Information Sheet, Tips and User Instructions (product catalogue) and / or our specifications (specific products) determines the content and the limits of our commitments regarding the technical features of our products.

Our F.I.C.C.U. (Information Sheet, Tips and User Instructions) can be obtained from your supplier.

You can also contact us via the email address: agricole@barbiergroup.com or on our website www.barbiergroup.com

Our recommendations

We recommend that before you order and use our films please:

- Read our Information Sheet, Tips and User Instructions.
- Discuss with your supplier our products for your specific operating conditions

Distributor Stamp

Special 3D | Combix



GROUPE BARBIER
LA GUIDE – BP 39
F 43602 SAINTE – SIGOLENE CEDEX
TELEPHONE : + 33.(0)4.71.75.11.11
FAX + 33.(0)4.71.66.15.01
Email : barbier@barbiergroup.com
Website : www.barbiergroup.com

Groupe
Barbier
Plastic solutions