

TRISILO™ Black

THREE LAYERS FILM:

- Mechanical resistance adapted to silage protection,
 - Excellent opacity,
 - 12 months UV protection $\leq 130\text{Kly}$: Class S1
- Coil packaged in a waterproof white sheath and very resistant.

We guarantee the respect of the reel surfaces according to the code of practice of the plastic film industries.

TECHNICAL SPECIFICATIONS

* Dart Test on film / on folds

Nominal Thickness	150 μ 180 μ on command	ISO 4591 & ISO 4593
Dart test*	250 g / 100 g	EN ISO7765-2004 Method A
Durability	12 months	
Stress at break	SL>17 Mpa / ST>17 Mpa	EN ISO 527-1
Elongation at break	SL>400% / ST>400%	EN ISO 527-3

Implementation Tips



To avoid any problems during unwinding, for this respect the instructions of unrolling. Avoid stepping on the film by unrolling it and unfolding it on the silo.



Your silo is a capital investment. To improve the conservation of your silos, use a 40 μ sub-film new generation 5 layers of the BARBIER range. This film will increase the effect of forage and will further limit the formation of air pockets.

Exclusivity of **Barbier** this film is guaranteed **Food Contact**.



Our Engagements

This commercial sheet has no contractual value. The information and photographs it contains do not commit us except for the technical specifications appreciated in accordance with the EN13207 standard.

Only our F.I.C.C.U. : Information Sheet, Advice and Instructions for Use (catalogue products) and / or our specifications (specific products) determines the content and limits of our commitments concerning the technical characteristics of our products.

Our F.I.C.C.U. (Information Sheet, Tips and Instructions for Use) can be obtained from your supplier.

You can also contact us to obtain it at the email address: agricole@barbiergroup.com or on our website www.barbiergroup.com

Our Recommendations

We recommend that before you order and use our film:

- without having read our Information Sheet, Advice and Instructions for use.
- without having discussed with your supplier our product and the particular conditions of your operation.

Ballasting with used tyres is prohibited, use weighting bags provided for this purpose.

The use of **TRISILO™** for protection of straw stock is to be avoided.

