



Stretch film BARSTRETCH XT

- Coextruded stretch film,
- 9 layers cast process,
- Adhesion on the inside (for outside please contact us)
- Specially designed for automatic wrapping of badly shaped load with a pre stretching of 290 to 380%.
- Width 500 mm, 750 mm or 1000 mm



Description

This high performance film allows great versatility. For heavy and irregular loads, with perforating corners, Barstretch XT film guarantees an optimal result. With a pre stretching up to 380%, it offers a significant reduction in cost per pallet. For a stretching capacity of 300 %, 1 meter of film on the roll becomes 4 meters on the pallet. The film does not suffer any loss of width, will not tear and retains its elastic memory to hold the load.



Size

- Standard thicknesses: 15, 17, 20 23 and 30 μm
- Standard lengths: adapted to a roll weight of 16 kg.

Packaging

- Width 500 mm : Stacking pallets 1000x1200x1200mm of 46 rolls, which are 736 kg (indoor storage)
- Width 1000 mm : Stacking pallets 1000x1200x1200mm of 20 rolls, which are 665 kg (indoor storage)

Standard colors

Opaque (for other colors please contact us)



Translucent (for other colors please contact us)



Size properties

	SPECIFICATIONS	TEST METHOD
Closed width	$\pm 5 \text{ mm}$	ISO 4592
Nomiale thickness	$\pm 0,5 \mu\text{m}$	ISO 4591
Spot thickness	$\pm 2 \mu\text{m}$	ISO 4593
Roll edge	$< 3 \text{ mm}$	ISO 4592
Winding variations	$< 2 \text{ mm}$	ISO 4592

Mechanical properties

	SPECIFICATIONS				
Nominal thickness (μm)	15	17	20	23	30
Elongation at break (%)					
- machine direction	490	510	530	550	600
- transverse direction	710	730	750	750	700
Dart impact test (g)	500	600	>600	>600	>1000
Tearing resistance (cN)					
- machine direction	150	180	200	230	300
- transverse direction	250	270	300	350	350